



FOAM NITRILE COATED CUT-RESISTANT GLOVES GCT-654 // SPECIFICATION SHEET



ATTRIBUTES:

- 13g Salt and Pepper HPPE/SS Shell
- Black MicroFoam Nitrile Palm Coating
- 1935g Cut Protection



FEATURES:

- Enhanced Grip in Oily and Greasy Environments

APPLICATIONS:

- Automotive Manufacturing
- Metal Stamping
- Steel Handling
- Construction
- Recycling

CARE INSTRUCTIONS:

Recommended washing temperature is between 40°C and 60°C (104 - 140°F) with mild detergent.

The drying process may cause felting on the fabric surface. Drying temperatures should not exceed 70°C (158°F)

SPECIFICATIONS

LINER MATERIALS	13g Salt and Pepper HPPE/SS A4 Shell
COATING MATERIALS	Black MicroFoam Nitrile
WRIST DESIGN	Continuous Knit
SIZES	SM-2X

PACKAGING						
CASE SIZE	SM	MD	LG	XL	2X	
PER CARTON	12 DZ	12 DZ	12 DZ	12 DZ	12 DZ	
CUFF COLOR	RED	YELLOW	BROWN	BLACK	BLUE	
ORIGIN	PRC	PRC	PRC	PRC	PRC	

PERFORMANCE LEVEL

EN388: 4242D	EN LEVEL 4 CUT RESISTANCE					
ABRASION	0	1	2	3	4	5
CUT	0	1	2	3	4	5
TEAR	0	1	2	3	4	5
PUNCTURE	0	1	2	3	4	5
CUT TDM TEST	A	B	C	D	E	F