



ATTRIBUTES:

- 13g Salt and Pepper HDPE Liner
- Gray Polyurethane Palm Coating



FEATURES:

- Positive Grip in Dry and Light Oil Environments

APPLICATIONS:

- Appliance Manufacturing
- Automotive Manufacturing
- Construction
- Sheet Metal Handling
- Small Parts Assembly

CARE INSTRUCTIONS:

Recommended washing temperature is between 40°C and 60°C (104 - 140°F) with mild detergent.

The drying process may cause felting on the fabric surface. Drying temperatures should not exceed 70°C (158°F)

⚠ This product can expose you to N,N-Dimethylformamide which is known to the State of California to cause cancer. For more information go to www.P65warnings.ca.gov

SPECIFICATIONS

LINER MATERIALS	13g Salt and Pepper HDPE A2 Liner
COATING MATERIALS	Gray Polyurethane
WRIST DESIGN	Continuous Knit
SIZES	SM-2X

PACKAGING						
CASE SIZE	SM	MD	LG	XL	2X	
PER CARTON	12 DZ	12 DZ	12 DZ	12 DZ	12 DZ	
CASE WEIGHT	17.85/lbs	18.84/lbs	20.06/lbs	20.83/lbs	22.48/lbs	
CUFF COLOR	RED	YELLOW	BROWN	BLACK	BLUE	
ORIGIN	PRC	PRC	PRC	PRC	PRC	

PERFORMANCE LEVEL

EN388: 4242B	EN LEVEL 2 CUT RESISTANCE					
ABRASION	0	1	2	3	4	5
CUT	0	1	2	3	4	5
TEAR	0	1	2	3	4	5
PUNCTURE	0	1	2	3	4	5
CUT TDM TEST	A	B	C	D	E	F