



PU COATED CUT-RESISTANT GLOVES
GCT-653 // SPECIFICATION SHEET



ATTRIBUTES:

- 13g Salt and Pepper HDPE Liner
- Gray Polyurethane Palm Coating



FEATURES:

- Positive Grip in Dry and Light Oil Environments

APPLICATIONS:

- Automotive Manufacturing
- Light Manufacturing
- Sheet Metal Handling
- Metal Stamping
- Construction

CARE INSTRUCTIONS:

Recommended washing temperature is between 40°C and 60°C (104 - 140°F) with mild detergent.

The drying process may cause felting on the fabric surface. Drying temperatures should not exceed 70°C (158°F)

This product can expose you to N,N-Dimethylformamide which is known to the State of California to cause cancer. For more information go to www.P65warnings.ca.gov

SPECIFICATIONS

LINER MATERIALS	13g Salt and Pepper HDPE A3 Liner
COATING MATERIALS	Gray Polyurethane
WRIST DESIGN	Continuous Knit
SIZES	MD-2X

PACKAGING						
CASE SIZE	MD	LG	XL	2X		
PER CARTON	12 DZ	12 DZ	12 DZ	12 DZ		
CASE WEIGHT	21.38/lbs	23.36/lbs	24.25/lbs	26.01/lbs		
CUFF COLOR	YELLOW	BROWN	BLACK	BLUE		
ORIGIN	PRC	PRC	PRC	PRC		

PERFORMANCE LEVEL

EN388: 4442C	EN LEVEL 3 CUT RESISTANCE					
ABRASION	0	1	2	3	4	5
CUT	0	1	2	3	4	5
TEAR	0	1	2	3	4	5
PUNCTURE	0	1	2	3	4	5
CUT TDM TEST	A	B	C	D	E	F